

2024

# RIDGE® XR HVAC



- MSRP  
**\$29,999**
- ICE GRAY
- METALLIC GRAYSTONE



| POWER                           |  | Details                      |  |
|---------------------------------|--|------------------------------|--|
| Engine                          | 4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled | Ground Clearance             | 13.8/14.6 in (max preload); 13.8 in CA Model   |
| Displacement                    | 999cc  | Fuel Capacity                | 12.9 gal   |
| Maximum Horsepower              | 116.0 hp <sup>1</sup> @ 8,500 rpm                            | Turning Radius               | 15.0 ft  |
| Maximum Torque                  | 73.8 lb-ft @ 8,000 rpm                                       | Cargo Bed Dimensions (LxWxH) | 34.6 x 49.0 x 12.8 in  |
| Bore x Stroke                   | 73.4 x 59.0mm  | Cargo Bed Load Capacity      | 1,000/600 lb CA Model  |
| Compression Ratio               | 10.6:1   | Payload Capacity             | 1,499/1,100 lb CA Model  |
| Fuel System                     | EFI  | Seating Capacity             | 2, bucket seat   |
| Ignition                        | TCBI with Digital Advance                                    | Towing Capacity              | 2,500 lbs  |
| Starting System                 | Electric   | Lighting                     | All-LED lighting   |
| Transmission                    | Continuously Variable Transmission (CVT) with (H,L,N,R)      | DETAILS                      |  |
| Final Drive                     | Selectable 4WD with locking front/rear differential, shaft   | Frame                        | Ladder type, tubular steel   |
| Engine Braking                  | Yes  | Overall Length               | 125.4 in   |
| Alternator Output (max)         | 85 amp   | Overall Width                | 64.0 in  |
| Electronic Rider Aids           | Power Modes, Economical Riding Indicator                     | Overall Height               | 82.3 in  |
| CAPABILITY                      |  | Estimated Dry Weight         | 1,960.3/1,962.5 lb** CA Model  |
| Front Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in                         | Curb Weight                  | 2,066.1/2,068.3 lb* CA Model   |
| Rear Suspension / Wheel Travel  | Long-Travel, Double Wishbone/12.7 in                         | Wheelbase                    | 90.7 in  |
| Front Tires                     | Duro 30 x 10-14  | Instruments                  | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Rear Tires                      | Duro 30 x 10-14  | Additional Features          | Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible  |
| Wheel Type                      | 14" Aluminum   | Color Choices                | Ice Gray, Metallic Graystone   |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS)             |                              |  |
| Front Brakes                    | Dual hydraulic 249mm discs with two-piston calipers          |                              |  |
| Rear Brakes                     | Dual hydraulic 249mm discs with single-piston calipers       |                              |  |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.