

2024

# TERYX KRX<sup>®</sup> 1000 eS

**Kawasaki**  
Let the Good Times Roll<sup>®</sup>



MSRP  
**\$23,399**

 ICE GRAY/METALLIC ONYX BLACK



## POWER

Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Displacement	999cc
Maximum Torque	76.7 lb-ft @ 7,000 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	11.5:1
Fuel System	DFI <sup>®</sup> with two 50mm throttle bodies
Ignition	TCBI with Electronic Advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

## CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in
Front Tires	Maxxis <sup>®</sup> Carnivore 31 x 10.00R15 8PR
Rear Tires	Maxxis <sup>®</sup> Carnivore 31 x 10.00R15 8PR
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	Dual hydraulic discs with two-piston calipers
Rear Brakes	Dual hydraulic discs with single-piston calipers
Ground Clearance	14.4 in (max), 14.0 in (std)

Fuel Capacity	10.6 gal
Turning Radius	20.3 ft
Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Cargo Bed Load Capacity	351 lb
Payload Capacity	781 lb
Seating Capacity	2
Towing Capacity	N/A
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight

## DETAILS

Frame	Ladder type, tubular steel
Overall Length	132.1 in
Overall Width	68.1 in
Overall Height	77.0 in
Curb Weight	1,944.8 lb* / 1,947.0 lb* CA Model
Wheelbase	98.8 in
Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Wheel Type	Alloy with bead-lock wheels
Additional Features	Roof, Front Bumper
Color Choices	Ice Gray/Metallic Onyx Black

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx<sup>®</sup> side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.