MULE PRO-DXT™ EPS





\$19,799



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 55 amp

(max)

Ground Clearance 10.2 in

7.9 gal **Fuel Capacity**

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH) person)

Cargo Bed Load

Capacity

Payload Capacity 1,574 lb

Seating Capacity 3-person (1-row), 6-person (2-row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Rear Tires

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12

26 x 11-12

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual disc, 2-piston caliper **Rear Brakes** Dual disc, 1-piston caliper

Independent, mechanical disc **Park Brake Type**

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1,942.6 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person)

Color Choices Super Black





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471