## **MULE PRO-DXT™ FE EPS**





MSRP **\$19,999** 



**BRIGHT WHITE** 



## **POWER**

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 55 amp

(max)

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH) person)

Cargo Bed Load

Capacity

999 lb (3-person) / 350 lb (6-person)

Payload Capacity 1,574 lb

Seating Capacity 3-person (1-row), 6-person (2-row)

Towing Capacity 2,000 lb

**Lighting** (2) Halogen headlights

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

 Front Tires
 26 x 9-12

 Rear Tires
 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual disc, 2-piston caliper
Rear Brakes Dual disc, 1-piston caliper

Park Brake Type Independent, mechanical disc

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.