MULE PRO-MX™ SE





\$15,499



GOLD



Independent, mechanical disc

10.6 in

9.5 gal

14.0 ft

2

1,500 lb

33.4 x 44.1 x 9.1 in

699 lb / 600 lb CA Model

1,200 lb / 1,100 lb CA Model

(2) Halogen headlights, (2) LED headlights

POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal **Transmission**

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

DETAILS

Lighting

Park Brake Type

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

Dimensions (LxWxH)

Cargo Bed

Capacity

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,622.9 lb* / 1,625.1 lb* CA Model

Wheelbase

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Additional Features Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels,

Painted Body Panels

Color Choices Gold

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone / 8.6 in

Rear Suspension / **Wheel Travel**

Double wishbone/9.1 in

Front Tires

25 x 8-12, radial

Rear Tires

25 x 10-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471