

NEW 2025

NINJA® 1100SX ABS

Kawasaki
Let the Good Times Roll®



MSRP
\$13,699

 METALLIC CARBON GRAY/METALLIC DIABLO BLACK



POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	1,099cc
Bore x Stroke	77.0 x 59.0mm
Compression Ratio	11.8:1
Maximum Horsepower	134.0 hp ¹ @ 9,000 rpm
Maximum Torque	83.2 lb-ft @ 7,600 rpm
Fuel System	DFI® with 38mm Electronic Throttle Valves
Ignition	TCBI with Digital Advance
Transmission	6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

Rear Suspension / Wheel Travel	Horizontal back-link, gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in
Front Tire	120/70-17
Rear Tire	190/50-17
Front Brakes	Dual 300mm discs with radial-mount 4-piston monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Rear Brakes	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in
---------------------------------	--

DETAILS

Frame Type	Twin-spar aluminum
Rake/Trail	24.0°/3.9 in
Overall Length	82.7 in
Overall Width	31.7 in
Overall Height	46.9 in/48.2 in w/ windshield high
Ground Clearance	5.3 in
Seat Height	32.3 in
Dry Weight	471.9 lb**
Curb Weight	518.2 lb*
Fuel Capacity	5.0 gal
Wheelbase	56.7 in
Special Features	4.3" All-digital TFT Instrumentation, All-LED lighting, USB Type-C outlet, Smartphone Connectivity with Voice Command via RIDEOLGY THE APP MOTORCYCLE
Color Choices	Metallic Carbon Gray/Metallic Diablo Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.