NINJA H2®R ABS





MSRP **\$59,100**



MIRROR COATED MATTE SPARK BLACK



POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 8.3:

Maximum Torque 121.5 lb-ft @ 12,500 rpm

Fuel System DFI® with 50mm throttle bodies (4) with dual injection;

Kawasaki Supercharger

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift, dog-ring

Final Drive Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and top-out spring/5.3 in

Front Tire 120/60-17 V01F slick

Rear Tire 190/65-17 V01R slick

Front Brakes Dual 330mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo M50 Monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Rake/Trail	25.1°/4.3 in
Overall Length	81.5 in

Overall Width 33.5 in

Overall Height 45.7 in

Ground Clearance 5.1 in

Seat Height 32.7 in

Dry Weight 432.2 lb**

Curb Weight 476.3 lb*

Fuel Capacity 4.5 gal

Wheelbase 571 in

Special Features Supercharged engine, Carbon fiber aerodynamic downforce generating devices, Highly Durable Paint

Color Choices Mirror Coated Matte Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.