NINJA® ZX™-14R ABS





\$17,599



METALLIC MATTE SOVEREIGN RED/METALLIC FLAT SPARK METALLIC MATTE GRAPHITE GRAY



POWER

4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-**Engine**

cooled

12 3.1

Displacement 1,441cc

Bore x Stroke 84.0 x 65.0mm

Compression

Ratio

197.0 hp1 @ 10,000 rpm

Maximum Horsepower

Maximum Torque

116.5 lb-ft @ 7,500 rpm

Fuel System

DFI® with 44mm Mikuni throttle bodies (4)

Ignition

TCBI with Electronic Advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock

Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride

height/4.9 in

Front Tire 120/70-17

Rear Tire 190/50-R17

Front Brakes Dual 310mm semi-floating Brembo discs with dual

radial-mounted Brembo 4-piston M50 monobloc

calipers and ABS

Single 250mm disc with twin-piston caliper and ABS **Rear Brakes**

DETAILS

Overall Height

Seat Height

Frame Type Aluminum monocoque

46.1 in

49 in

31.5 in

Rake/Trail 23.0°/3.7 in

Overall Length 85.4 in

Overall Width 30.3 in

Ground Clearance

Curb Weight 593.1 lb*

Fuel Capacity 5.8 gal

Wheelbase 58.3 in

Color Choices Metallic Matte Sovereign Red/Metallic Flat Spark

Black/Metallic Matte Graphite Gray

Scan with camera to view videos, key features and more.

