NINJA® ZX™-4RR ABS





MSRP \$9,699



METALLIC MATTE WHITISH SILVER/ METALLIC FLAT SPARK BLACK



POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve,

liquid-cooled

Displacement 399cc

Bore x Stroke 57.0 x 39.1mm

Compression

Ratio

12.3:1

Maximum Torque 26.5 lb-ft @ 11,000 rpm

DFI® with 34mm throttle valves (4) **Fuel System**

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift

Final Drive Chain

Electronic Rider

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock

Brake System (ABS)

PERFORMANCE

Front Suspension / **Wheel Travel** 37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link, Showa BFRC lite gascharged shock w/ piggyback reservoir, adjustable compression, rebound and spring

preload/4.9 in

Rear Tire 160/60-17

Front Brakes Dual 290mm semi-floating discs with radial-

mount 4-piston monobloc caliper and ABS

Single 220mm disc with single-piston caliper **Rear Brakes**

and ABS

110/70-17

DETAILS

Front Tire

Frame Type Trellis, high-tensile steel

23.5°/3.8 in Rake/Trail

Overall Length 78.3 in

Overall Width 30.1 in

Overall Height 43.7 in

Ground 5.3 in Clearance

Seat Height 31.5 in

Curb Weight 414.5 lb*

Fuel Capacity 4.0 gal

Wheelbase 54.3 in

Special Features 4.3" Full-color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Matte Whitish Silver/Metallic Flat Spark

Black



