## 2025 **RIDGE<sup>®</sup> LIMITED HVAC**







## **POWER**

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	
Displacement	999cc	
Maximum Horsepower	92.0 hp1 @ 8,500 rpm	
Maximum Torque	65.8 lb-ft @ 5,500 rpm	
Bore x Stroke	73.4 x 59.0mm	
Compression Ratio	10.6:1	
Fuel System	EFI	
Ignition	TCBI with Digital Advance	
Starting System	Electric	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 4WD with locking rear differential, shaft	
Engine Braking	Yes	
Alternator Output (max)	85 amp	
Electronic Rider Aids	Power Modes, Economical Riding Indicator	

12.4/13.6 in (max preload); 12.4 in CA Model	
12.9 gal	
15.0 ft	
34.6 x 49.0 x 12.8 in	
1,000/600 lb CA Model	
1,191/792 lb CA Model	
3, bench seat	
2,500 lb	
All-LED lighting	

## DETAILS

	Selectable 4WD with locking rear differential, shaft	Frame	Ladder type, tubular steel	
g	Yes	Overall Length	128.9 in	
tput	85 amp	Overall Width	64.0 in	
ler Aids	Power Modes, Economical Riding Indicator	Overall Height	81.1 in	
		Estimated Dry Weight	2,024.2/2,024.4 lb** CA Model	
LITY		Curb Weight	2,130.0/2,132.2 lb* CA Model	
sion /	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in	
ion /	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery	
	Duro 27 x 9-14		voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and	
	Duro 27 x 11-14		warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)	
	14" Aluminum	Additional Features	8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab	
	Rack-and-pinion w/ Electric Power Steering (EPS)		with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY	
	Dual hydraulic 249mm discs with two-piston calipers		THE APP Powersports, USB ports, KQR™ system compatible	
	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Metallic Shadow Gold	



CAPABIL

**Front Suspensi** Wheel Travel

**Rear Suspensio** Wheel Travel

**Front Tires** 

**Rear Tires** Wheel Type

Steering

**Front Brakes Rear Brakes** 



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.

