

ALL-NEW 2025

RIDGE® XR CREW HVAC

Kawasaki

Let the Good Times Roll®



MSRP

\$33,099

- ICE GRAY
- METALLIC GRAYSTONE



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Ground Clearance	14.4/15.2 in (max preload); 14.4 in CA Model
Displacement	999cc	Fuel Capacity	12.9 gal
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm	Turning Radius	19.0 ft
Maximum Torque	73.8 lb-ft @ 8,000 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Bore x Stroke	73.4 x 59.0mm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Compression Ratio	10.6:1	Payload Capacity	1,290/1,076 lb CA Model
Fuel System	EFI	Seating Capacity	4-person (2 row), bucket seats
Ignition	TCBI with Digital Advance	Towing Capacity	2,500 lb
Starting System	Electric	Lighting	All-LED lighting
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)		
Final Drive	Selectable 4WD with locking front/rear differential, shaft		
Engine Braking	Yes	Frame	Ladder type, tubular steel
Alternator Output (max)	85 amp	Overall Length	156.7 in
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Overall Width	64.0 in
CAPABILITY		Overall Height	82.7 in
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Dry Weight	2,403.5/2,405.7 lb** CA Model
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Curb Weight	2,513.7/2,515.9 lb* CA Model
Front Tires	Duro 30 x 10-14	Wheelbase	122.2 in
Rear Tires	Duro 30 x 10-14	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Wheel Type	14" Aluminum	Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	Color Choices	Ice Gray, Metallic Graystone
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [Kawasaki.com](#) for full product details.