2025 **RIDGE[®] XR DELUXE HVAC**







POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm
Maximum Torque	73.8 lb-ft @ 8,000 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking front/rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

Ground Clearance	13.8/14.6 in (max preload); 13.8 in CA Model
Fuel Capacity	12.9 gal
Turning Radius	15.0 ft
Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Cargo Bed Load Capacity	1,000/600 lb CA Model
Payload Capacity	1,275/875 lb CA Model
Seating Capacity	3, bench seat
Towing Capacity	2,500 lb
Lighting	All-LED lighting

DETAILS

Final Drive	Selectable 4WD with locking front/rear differential, shaft	Frame	Ladder type, tubular steel	
Engine Braking	Yes	Overall Length	125.4 in	
Alternator Output (max)	85 amp	Overall Width	64.0 in	
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Overall Height	82.3 in	
		Estimated Dry Weight	1,964.7/1,966.9 lb** CA Model	
CAPABILITY		Curb Weight	2,070.5/2,072.7 lb* CA Model	
Front Suspension /	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in	
Wheel Travel Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator,	
Front Tires	Duro 30 x 10-14		maintenance reminder, high beam, neutral, reverse, and	
Rear Tires	Duro 30 x 10-14		warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)	
Wheel Type	14" Aluminum	Additional Features	Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-	
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		FIT [®] , Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports,	
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		KQR™ system compatible	
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Ice Gray, Metallic Graystone	





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.