

2025

TERYX® KRX4™ 1000 BLACKOUT EDITION

Kawasaki

Let the Good Times Roll®

MSRP

\$28,999

 FLAT EBONY



POWER	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled
Displacement	999cc
Maximum Torque	75.2 lb-ft @ 7,000 rpm
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	11.5:1
Fuel System	DFI® with (2) 50mm throttle bodies
Ignition	TCBI with electronic advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

CAPABILITY	
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	Dual hydraulic discs with 2-piston calipers
Rear Brakes	Dual hydraulic discs with single-piston calipers
Ground Clearance	13.8 in (max), 13.2 in (std)
Fuel Capacity	10.6 gal
Turning Radius	23.3 ft

Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Cargo Bed Load Capacity	351 lb
Payload Capacity	1,001 lb
Seating Capacity	4
Towing Capacity	N/A
Lighting	(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars

DETAILS	
Frame	Ladder type, tubular steel
Overall Length	160.4 in
Overall Width	68.1 in
Overall Height	78.0 in
Estimated Dry Weight	2,152.1 lb** / 2,154.3 lb** CA Model
Curb Weight	2,253.5 lb* / 2,257.7 lb* CA Model
Wheelbase	125.8 in
Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Wheel Type	Alloy
Additional Features	LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch
Color Choices	Flat Ebony

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.