## **VERSYS® 1100 SE LT ABS**





\$19,499



METALLIC GRAPHITE GRAY/METALLIC DIABLO BLACK



## **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, liquid-cooled

Displacement 1.099cc

**Bore x Stroke** 77.0 x 59.0mm

**Compression Ratio** 11.8:1

Maximum 133.0 hp1 @ 9,000 rpm

Horsepower

**Maximum Torque** 82.5 lb-ft @ 7,600 rpm

**Fuel System** DFI® with 38mm throttle bodies (4)

Ignition TCBI with Electronic Advance

**Transmission** 6-speed, return shift with wet multi-disc manual Assist &

Slipper Clutch

**Final Drive** Chain

**Electronic Rider Aids** Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Kawasaki Electronic Control Suspension (KECS), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis

**Orientation Awareness** 

## **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in

Rear Suspension / **Wheel Travel** 

Horizontal back-link, Showa BFRC Lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring

preload/5.9 in

**Front Tire** 120/70-17 **Rear Tire** 180/55-17

**Front Brakes** Dual 310mm petal discs with radial-mount 4-piston

monobloc calipers, Kawasaki Intelligent anti-lock Brake

System (KIBS)

**Rear Brakes** Single 260mm petal disc with single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

## **DETAILS**

Weight

**Frame Type** Twin-tube, aluminum

Rake/Trail 27.0°/4.0 in **Overall Length** 89.4 in **Overall Width** 37.4 in

**Overall Height** 60.2 in (windshield Hi) / 59.8 in (windshield Lo)

**Ground Clearance** 5.9 in **Seat Height** 33.1 in

**Estimated Dry** 520.4 lb\*\* (+20 lb w/ saddlebags)

**Curb Weight** 571.1 lb\* (+20 lb w/ saddlebags)

**Fuel Capacity** 5.5 gal

Wheelbase 59.8 in

**Special Features** Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, USB Type-C outlet, Adjustable

windshield, Grip heaters and hand guards, ERGO-FIT®, Highly Durable Paint, Smartphone Connectivity with Voice Command via RIDEOLOGY THE APP MOTORCYCLE

Metallic Graphite Gray/Metallic Diablo Black **Color Choices** 

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.