

NEW 2026

BRUTE FORCE® 750 SE EPS CAMO

Kawasaki

Let the Good Times Roll®



MSRP

\$13,299

TRUETIMBER® STRATA



| POWER | | Steering | Rack-and-pinion w/ Electric Power Steering (EPS) |
|---------------------------------|---|---------------------------|--|
| Engine | 4-stroke, V-twin, SOHC, liquid-cooled | Turning Radius | 10.5 ft |
| Displacement | 749cc | Towing Capacity | 1,250 lb |
| Bore x Stroke | 85.0 x 66.0mm | Total Rack Capacity | 264.5 lb |
| Compression Ratio | 9.3:1 | Rack Capacity, Front/Rear | 88.0/176.0 lb |
| Maximum Torque | 42.8 lb-ft @ 4,750 rpm | Lighting | All-LED lighting |
| Fuel System | DFI® with two 34mm throttle bodies | DETAILS | |
| Ignition | Digital DC-CDI | Frame Type | Double-cradle, high-tensile tubular steel |
| Transmission | Automatic Continuously Variable Transmission (CVT) with (H,L,N,R) | Tread Width | 37.0/35.6 in |
| Final Drive | Selectable 2WD/4WD with variable control front differential lock, shaft | Overall Length | 88.4 in |
| CAPABILITY | | Overall Width | 46.7 in |
| Front Suspension / Wheel Travel | Double wishbone, adjustable spring preload/6.9 in | Overall Height | 47.8 in |
| Rear Suspension / Wheel Travel | Double wishbone, adjustable spring preload/7.4 in | Seat Height | 35.2 in |
| Front Tire | AT 25 x 8-12 | Dry Weight | 723.2 lb** |
| Rear Tire | AT 25 x 10-12 | Curb Weight | 769.5 lb* |
| Front Brakes | Dual hydraulic 176mm discs with 2-piston calipers | Wheelbase | 50.6 in |
| Rear Brakes | Sealed, oil-bathed, multi-disc with independent park brake | Instruments | Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage) |
| Ground Clearance | 8.7 in/9.6 in (max preload) | Special Features | WARN® VRX 25-S Powersport Winch, Front brush guard, Hand guards, Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLGY THE APP POWERSPORTS, KQR™ system |
| Starting System | Electric | Color Choices | TRUETIMBER® STRATA |
| Fuel Capacity | 5.0 gal | | |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.