



2026

KLX[®]300SM



MSRP
\$5,849

-  NEON GREEN/EBONY
-  BATTLE GRAY/EBONY



POWER

Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	292cc
Bore x Stroke	78.0 x 61.2mm
Compression Ratio	11.1:1
Maximum Torque	17.7 lb-ft @ 7,000 rpm
Fuel System	DFI [®] with 34mm Keihin throttle body
Ignition	CDI
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping/9.1 in
Rear Suspension / Wheel Travel	Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/8.1 in

Front Tire	110/70-17
Rear Tire	130/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

DETAILS

Frame Type	Tubular, semi-double cradle
Rake/Trail	25.0°/2.8 in
Overall Length	83.3 in
Overall Width	31.1 in
Overall Height	44.7 in
Ground Clearance	9.3 in
Seat Height	33.9 in
Dry Weight	286.6 lb**
Curb Weight	304.3 lb*
Fuel Capacity	2.0 gal
Wheelbase	56.5 in
Color Choices	Neon Green/Ebony, Battle Gray/Ebony

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.