

2026

KX™ 250



MSRP
\$8,999



POWER

Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain
Electronic Rider Aids	Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode

PERFORMANCE

Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 16-way compression and rebound damping /12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (4 turns high speed /19-way low-speed) compression damping, 22-way rebound damping and adjustable preload /12.1 in

Front Tire	80/100-21
Rear Tire	110/90-19
Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking petal disc with single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	27.0° /4.6 in
Overall Length	86.2 in
Overall Width	32.3 in
Overall Height	49.8 in
Ground Clearance	13.4 in
Seat Height	37.6 in
Curb Weight	230.9 lb* without fuel / 240.8 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.