MULE PRO-FX™ 1000 HD EDITION





\$17,699



FIRECRACKER RED



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement

61.5 lb-ft @ 4,500 rpm **Maximum Torque**

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

Fuel System DFI® with 38mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking

Alternator Output 90 amp

(max)

Ground Clearance 11.9 in (max), 11.8 in (std)

Fuel Capacity 7.9 gal

Turning Radius

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

999/600 lb CA Model

54.1 x 53.3 x 11.0 in

Payload Capacity 1,616.3/1,263.5 lb CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires 26 x 9-12, radial **Rear Tires** 26 x 11-12, radial

Wheel Type Steel

Steering Rack-and-pinion

Front Brakes Dual disc, 2-piston caliper

Dual disc, 1-piston caliper Rear Brakes

Park Brake Type Independent, mechanical disc

DETAILS

Overall Height

Overall Length 136.6 in **Overall Width** 64.0 in

81.1 in **Dry Weight** 1,830.2/1,832.4 lb** CA Model

Curb Weight 1,913.9/1,916.1 lb* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

Additional Features

Roof, Rear Bumper, Additional Under Seat Storage Bin, Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling

Rear Suspension, Anti-cinch Seatbelts

Color Choices Firecracker Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.