MULE PRO-MX™ EPS





MSRP **\$14,099**



GRAY



FIRECRACKER RED



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio

Fuel System DFI® with 44mm throttle body

10.3:1

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

35.7 amp

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.6 in

Rear Suspension / Wheel Travel Double wishbone/9.1 in

Front Tires 2

25 x 8-12, radial 25 x 10-12, radial

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Park Brake Type Independent, mechanical disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

Cargo Bed Load

Payload Capacity

Capacity

1,200 lb / 1,100 lb CA Model

Seating Capacity 2

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 74.4 in

Dry Weight 1,512.6 lb** / 1,514.8 lb** CA Model

Curb Weight 1,587.6 lb* / 1,589.8 lb* CA Model

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning

indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Color Choices Gray, Firecracker Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.