## **MULE PRO-MX™ EPS**





**MSRP** \$14,099



**GRAY** 



FIRECRACKER RED



## **POWER**

4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled **Engine** 

695cc Displacement

**Maximum Horsepower** 44.0 hp1 @ 6,000 rpm **Maximum Torque** 42.7 lb-ft @ 5,000 rpm

102.0 x 85.0mm Bore x Stroke

**Compression Ratio** 10.3:1

DFI® with 44mm throttle body **Fuel System** 

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential with

**Engine Braking** Yes

**Alternator Output** 

(max)

35.7 amp

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone /8.6 in

Rear Suspension / **Wheel Travel** 

**Rear Tires** 

Double wishbone/9.1 in

**Front Tires** 25 x 8-12, radial

25 x 10-12, radial Electric Power Steering (EPS), Tilt steering Steering

**Front Brakes** Dual disc, 2-piston caliper **Rear Brakes** Dual disc, 1-piston caliper

**Ground Clearance** 10.6 in **Fuel Capacity Turning Radius** 

**Cargo Bed Dimensions** 33.4 x 44.1 x 9.1 in (LxWxH)

Cargo Bed Load

**Park Brake Type** 

Capacity

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

Lighting

Independent, mechanical disc

9.5 gal 14.0 ft

699 lb / 600 lb CA Model

1,200 lb / 1,100 lb CA Model

2

1,500 lb

(2) Halogen headlights, (2) LED headlights

## **DETAILS**

**Overall Length** 110.0 in **Overall Width** 60.0 in **Overall Height** 74.4 in

**Estimated Dry Weight** 1,512.6 lb\*\* / 1,514.8 lb\*\* CA Model 1,587.6 lb\* / 1,589.8 lb\* CA Model **Curb Weight** 

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

**Color Choices** Gray, Firecracker Red

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.