

2026

MULE PRO-MX™ LE

Kawasaki

Let the Good Times Roll®

MSRP

\$14,699

DEEP BLUE



POWER		DETAILS	
Engine	4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled	Park Brake Type	Independent, mechanical disc
Displacement	695cc	Ground Clearance	10.6 in
Maximum Torque	42.7 lb-ft @ 5,000 rpm	Fuel Capacity	9.5 gal
Bore x Stroke	102.0 x 85.0mm	Turning Radius	14.0 ft
Compression Ratio	10.3:1	Cargo Bed Dimensions (LxWxH)	33.4 x 44.1 x 9.1 in
Fuel System	DFI® with 44mm throttle body	Cargo Bed Load Capacity	699 lb / 600 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)	Payload Capacity	1,200 lb / 1,100 lb CA Model
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Seating Capacity	2
Engine Braking	Yes	Towing Capacity	1,500 lb
Alternator Output (max)	35.7 amp	Lighting	(2) Halogen headlights, (2) LED headlights
CAPABILITY		Overall Length	110.0 in
Front Suspension / Wheel Travel	Double wishbone/8.6 in	Overall Width	60.0 in
Rear Suspension / Wheel Travel	Double wishbone/9.1 in	Overall Height	75.8 in
Front Tires	25 x 8-12, radial	Dry Weight	1,519.2 lb** / 1,521.4 lb** CA Model
Rear Tires	25 x 10-12, radial	Curb Weight	1,594.2 lb* / 1,596.4 lb* CA Model
Steering	Electric Power Steering (EPS), Tilt steering	Wheelbase	78.9 in
Front Brakes	Dual disc, 2-piston caliper	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
Rear Brakes	Dual disc, 1-piston caliper	Additional Features	Roof, Cast Aluminum Wheels
		Color Choices	Deep Blue

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.