

2026

TERYX KRX[®] 1000 BLACKOUT EDITION

Kawasaki

Let the Good Times Roll[®]



MSRP

\$26,399

 FLAT EBONY



POWER		DETAILS	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Turning Radius	20.3 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Horsepower	110.0 hp ¹ @ 8,500 rpm	Cargo Bed Load Capacity	351 lb
Maximum Torque	75.2 lb-ft @ 7,000 rpm	Payload Capacity	781 lb
Bore x Stroke	92.0 x 75.1mm	Seating Capacity	2
Compression Ratio	11.5:1	Towing Capacity	N/A
Fuel System	DFI [®] with (2) 50mm throttle bodies	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars
Ignition	TCBI with electronic advance		
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
CAPABILITY			
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Frame	Ladder type, tubular steel
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Overall Length	133.3 in
Front Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR	Overall Width	68.1 in
Rear Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR	Overall Height	76.0 in
Steering	Electric Power Steering (EPS) / rack-and-pinion	Estimated Dry Weight	1,931.6 lb** / 1,933.8 lb** CA Model
Front Brakes	258mm dual hydraulic discs with 2-piston calipers	Curb Weight	2,030.8 lb* / 2,033.0 lb* CA Model
Rear Brakes	258mm dual hydraulic discs with single-piston calipers	Wheelbase	98.8 in
Ground Clearance	14.0 in (max), 13.4 in (std)	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Fuel Capacity	10.6 gal	Additional Features	LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR [™] Premium Roof, Hifonics [®] Audio System, WARN [®] VRX 45 Powersport Winch
		Color Choices	Flat Ebony

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.