

ALL-NEW 2026

TERYX[®] 5 H2 DELUXE eS

Kawasaki

Let the Good Times Roll[®]

MSRP

\$43,699

LIME GREEN



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Fuel Capacity	14.8 gal
Displacement	999cc	Turning Radius	24.9 ft
Maximum Horsepower	250.0 hp ¹ @ 9,000 rpm	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Torque	146.3 lb-ft @ 8,800 rpm	Cargo Bed Load Capacity	300 lb
Bore x Stroke	73.4 x 59.0mm	Payload Capacity	1,076 lb
Compression Ratio	7.8:1	Seating Capacity	5-person (2 row), front bucket seats and rear contoured sport bench seat with 4-point seatbelts
Fuel System	DFI [®] with (4) 40mm throttle bodies with dual injection; Kawasaki Supercharger	Lighting	All-LED lighting
Ignition	TCBI with electronic advance	Instruments	
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Frame	Ladder type, tubular steel
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Length	159.4 in
Engine Braking	Yes	Overall Width	74.0 in
CAPABILITY		Overall Height	73.8 in / 78.5 in (with antenna)
		Estimated Dry Weight	2,372.6 lb** / 2,374.8 lb** CA Model
Front Suspension / Wheel Travel	Double wishbone, FOX 3.0 Live Valve Internal Bypass shocks with piggyback reservoir, KECS-controlled compression damping, and manually adjustable spring preload/23.2 in	Curb Weight	2,507.1 lb* / 2,509.3 lb* CA Model
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 3.0 Live Valve Internal Bypass shocks with piggyback reservoir, KECS-controlled compression damping, and manually adjustable spring preload/24.0 in	Wheelbase	126.0 in
Front Tires	Maxxis [®] Carnivore Plus 33 x 10.00R16	Additional Features	
Rear Tires	Maxxis [®] Carnivore Plus 33 x 10.00R16		
Steering	Electric Power Steering (EPS) / rack-and-pinion	Color Choices	Lime Green
Front Brakes	270mm dual hydraulic discs with 3-piston calipers		
Rear Brakes	270mm dual hydraulic discs with 2-piston calipers		
Ground Clearance	16.5 in (max) / 16.1 in (std)		

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.